

FAR Armida



Cod 	Format 	Latime 	Lungime 	Compozitie 	Greutate
FAR	rola	280 cm	± 30 m	100 % polyester + verso acrilic	420 g/m ²

Reactie la foc 	IFR - IGNIFUGAT PERMANENT rezistent la foc si nu intretine arderea
--------------------	---

Certificat de ignifugare 	UNI 9177 clasa 1 EN 13773 clasa 1 DIN 4102 clasa B1 IMO 0497/19
------------------------------	--

Culori personalizate	Nu sunt disponibile la cerere
----------------------	-------------------------------

Grad de opacitate	● ● ● ● ●
Grad de absorbtie a luminii	● ● ○ ○ ○
Rezistenta la frecare	● ● ● ● ● >150.000 c Martindale
Pentru pictura	● ● ○ ○ ○
Pentru print digital	● ● ● ● ●
Absorbția sunetului • Montaj Tip G-100 (100 mm fata de peretele reflexiv)	● ● ○ ○ ○ Conform ISO 11654 Coeficient masurat de absorbtie a sunetului: $\alpha_w = 0.20$ Clasa de absorbtie a sunetului: E
Bariera fonica	● ● ● ● ○ Conform ISO 16283 Conform ASTM E413

Disponibilitate	la metru la rola confectionate la cerere
-----------------	--

