



Cod 	Format 	Latime 	Lungime 	Compozitie 	Creutate
FMI	rola	140 cm	± 30 m	100 % bumbac	600 g/m ²

Reactie la foc 	FR- IGNIFUGAT Tratatamentul ignifug este solubil in apa. Materialul NU se spala cu apa si trebuie folosit si pastrat in spatii curate, uscate, aerisite, ferite de caldura, soare si vreme nefavorabila
--------------------	--

Certificat de ignifugare 	EN 13501-1 clasa B s2 do NFP 92-503 class M1
------------------------------	---

Grad de opacitate	● ● ● ● ●
Grad de absorbtie a luminii	● ● ● ● ●
Rezistenta la frecare	● ● ● ● ● – >100.000 c Martindale
Pentru pictura	● ● ● ○ ○
Absorbtia sunetului • Montaj Tip G-150 (150 mm fata de peretele reflexiv)	● ● ● ● ● Conform ISO 11654 Coeficient masurat de absorbtie a sunetului: $\alpha_w = 0.50$ (H) Clasa de absorbtie a sunetului: D Conform ASTM C423 Coeficient de reducere a zgomotului: NRC = 0.45
Bariera fonica	● ● ● ○ ○ Conform ISO 16283 Conform ASTM E413

Disponibilitate	la metru la rola confectionate la cerere
-----------------	--

Culori personalizate	Disponibile la cerere Cantitate minima ± 300 ml
----------------------	--

Mod de curatare	
-----------------	--