

FFE Fedora



Cod 	Format 	Latime 	Lungime 	Compozitie 	Greutate
FFE	rola	295 cm	± 28 m	100 % poliester	315 g/m ²

Reactie la foc 	IFR - IGNIFUGAT PERMANENT rezistent la foc si nu intretine arderea
--------------------	---

Certificat de ignifugare 	UNI 9177 clasa 1 EN 13773 clasa 1 DIN 4102 clasa B1 NFP 92 503-507 clasa M1 BS 5867 part 2 tip B & C IMO FTP Code 2010 - Part 7
------------------------------	--

Grad de opacitate	●●●○○ ●●●●● -cu captuseala
Grad de absorbtie a luminii	●●●○○
Rezistenta la frecare	●●●●○ - >80.000 c Martindale
Pentru pictura	●●○○○
Pentru print digital	●●●●○
Absorbția sunetului • Montaj Tip G-100 (100 mm fata de peretele reflexiv)	●●●●○ Conform ISO 11654 Coeficient masurat de absorbtie a sunetului: aw = 0.60 (MH) Clasa de absorbtie a sunetului: C
Bariera fonica	●●○○○ Conform ISO 16283 Conform ASTM E413



Disponibilitate	la metru la rola confectionate la cerere
Culori personalizate	Disponibile la cerere Cantitate minima \pm 300 ml

